



Europe

Lead-free

Thanks to Ames Lab Innovation

Lead-free solder licensed worldwide as EU lead-free rules take effect

BY KERRY GIBSON

LEAD HAS LONG BEEN RECOGNIZED AS A highly toxic material that can cause brain damage. Its use in paint was banned in 1978, and it was later removed from gasoline to further protect human health. But a burgeoning source – electronic waste – poses a substantial new threat to the environment as lead and other chemicals leach from computers, cell phones and other electronic devices being buried in landfills.

Effective July 1, the European Union began strictly limiting the amount of lead and other hazardous materials lurking within the circuitry of any electronic appliance sold.¹ Given the global nature of the electronics industry, however, the European ban is in essence international in scope. As electronics and appliance manufacturers scrambled to meet those tough new restrictions, a lead-free solder developed several years ago at Ames Laboratory played a key role.

Shiny glue

Solder is the shiny metallic “glue” that holds components on circuit boards and bonds other electrical connections. Though a computer’s circuit boards contain only small amounts of lead solder, the problem is overall volume. By some estimates, about 3,000 tons of electronic waste is discarded daily just in the United States.

Composed of lead and tin, traditional solder melts and flows easily, but sets up quickly to create a strong, durable bond between the mating surfaces. A solder blend of 63 percent tin and 37 percent lead results in a eutectic alloy – one that acts like a pure metal with a single melting (and solidification) point.

“Finding a substitute for lead that gave the solder similar properties was difficult,” says Ames Laboratory senior metallurgist Iver Anderson. “With our basic understanding of alloys, we developed a tin-silver-copper alloy that offered a lower melting temperature and greater strength than other lead-free alternatives being considered.”

Big bucks

The Ames Laboratory’s solder technology was patented in 1996, and nearly 60 companies worldwide have licensed Ames Lab’s lead-free solder, according to Ken

Kirkland, executive director of the Iowa State University Research Foundation. To date, those licenses have generated royalties in excess of \$7 million. ISURF holds the patents for research developed at Iowa State, including Ames Laboratory.

"With the European directives and a similar commercial initiative in Japan, we've seen a growing interest in the alloy," Kirkland says. "The technology was a little ahead of its time, but it's an excellent product and we have a strong patent; you can't ask for a better combination than that."

The Ames Lab solder is just one of several lead-free alternatives on the market. The type and specific composition of lead-free solder also depends on the soldering technique used and the end application. In addition to the tin-silver-copper alloy, Anderson's group developed modified alloys that also contain iron, cobalt and other similar elements. These blends are suitable for higher-temperature applications and have also been patented by ISURF.

Battling brittleness

One ongoing problem with lead-free alternatives now available is their tendency to get brittle over time after repeated or prolonged heating cycles. And heat has become a growing factor as technological advances have boosted operating temperatures. For example, the steady climb in computer processor speeds has meant a corresponding increase in the amount of heat they generate. And computers aren't the only devices that generate heat.

"Even the circuitry in your cell phone operates at about 125 degrees Celsius," Anderson says, "and over six months' use, that can mean several hundred hours of high tempera-

tures. If you drop it now, the solder joints have become more brittle and the risk of it 'breaking' is higher."

To combat this solder "aging" problem, Anderson's group has recently been studying more additives to the tin-silver-copper formula, including silicon, titanium, chromium, manganese, nickel, zinc and germanium. Joints soldered with the different alloys were subjected to 150 C for 1,000 hours, then tested for both shear strength and impact strength.

"Zinc appears to be most attractive in terms of retained ductility and strength," Anderson says, "and also offers benefits in terms of solderability, ease of alloying and material cost." While additional testing is needed, he adds that the tin-silver-copper-zinc composition is covered under the original patent.

Added bonus

One other benefit of this recent work is development of a simple technique for characterizing the bulk composition of solder joints using an electron microprobe. This permits Anderson's research team to analyze the new compositions being studied under different soldering conditions.

"With the elimination of lead, tin-silver-copper solders are here for the long run," Anderson says. "But that doesn't mean we'll stop trying to improve our basic understanding of how these alloys work in order to improve their performance."

Q

¹ -The Waste Electrical and Electronic Equipment directive and the Restriction of Hazardous Substances directive.

For more information:

Iver Anderson, (515) 294-9791
andersoni@ameslab.gov

Research funded by:

DOE Office of Basic Energy Sciences,
Materials Science and
Engineering Division

